

XG3-15kW

Three Phase On-Grid Solar Inverter



Efficient Higher revenue

- 2MPP Trackers, high single circuit tracking accuracy, fast dynamic response.
- 160% DC Input Oversizing
- Wide MPPT voltage range: 180V-1000V
- Compatible with high power modules



Intelligent Simple O&M

- Smart I-V Curve Diagnosis Function: locate PV string faults accurately and automatically detect faults
- Intelligent Fault Detection: ac-side voltage and current waveforms real-time recorded, fast fault location
- Support RS485/USB (WiFi/GPRS/Ethernet optional): remote monitoring and operation via PC or mobile phones



Reliable Worry free

- IP66 Protection degree: support outdoor installation
- DC & AC Type II SPD: prevent lightning damage
- AFCI Function (Optional): when an arc-fault is detected the inverter immediately stops operation

	XG3KTR	XG4KTR	XG5KTR	XG6KTR	XG8KTR	XG9KTR	XG10KTR	XG11KTR	XG12KTR	XG15KTR1
Input (DC)										
Max. Input Power	4.8kW	6.4kW	8kW	9.6kW	12.8kW	14.4kW	16kW	17.6kW	19.2kW	24kW
Max. Input Voltage	1100V									
Start Voltage	160V									
Rated Input Voltage	600V									
Full-load MPP Voltage Range	250V ~ 850V				320V ~ 850V	400V ~ 850V	450V ~ 850V		480V ~ 850V	500V ~ 850V
MPPT Voltage Range	180V ~ 1000V									
Number of MPP Trackers	2									
Number of String per MPPT	1 / 1									1 / 2
Max. Current per MPPT	14A / 14A									14A / 28A
Max. Short Circuit Current per MPPT	18A / 18A									18A / 36A
Output (AC)										
Max. Output Current	4.8A	6.4A	8A	9.6A	12.8A	14.4A	15.9A	17.5A	19.1A	23.9A
Rated Output Power	3kW	4kW	5kW	6kW	8kW	9kW	10kW	11kW	12kW	15kW
Max. Output Power	3.3kVA	4.4kVA	5.5kVA	6.6kVA	8.8kVA	9.9kVA	11kVA	12.1kVA	13.2kVA	16.5kVA
Rated Grid Frequency	50Hz / 60Hz									
Rated Grid Voltage	230Vac / 400Vac, 3L / N / PE									
Power Factor	>0.99 (0.8 leading~0.8 lagging)									
THDi	<3% (Rated Power)									
Efficiency										
Max. Efficiency	98.40%				98.70%					
European Efficiency	98.30%				98.50%					
MPPT Efficiency	99.90%									
Protection										
DC reverse polarity protection						Yes				
Anti-islanding protection						Yes				
AC short circuit protection						Yes				
Residual current monitoring unit						Yes				
Insulation resistance monitoring						Yes				
Ground fault monitoring						Yes				
Grid monitoring						Yes				
Surge protection						Type II				
AFCI protection						Optional				
Communication										
Display	LED / LCD (Optional)									
Communication	Standard: RS485 / USB Optional: WiFi / GPRS / Ethernet									
Standard Compliance										
Grid Connection Standards	IEC 61727, IEC 62116, IEC 60068, IEC 61683, VDE-AR-N 4110:2018, VDE-AR-N 4105:2018, VDE-AR-N 4120:2018, EN 50549, AS/NZS 4777.2:2020, CEI 0-21, VDE 0126-1-1/A1 VFR 2014, UTE C15-712-1:2013, DEWA DRRG, NRS 097-2-1, MEA/PEA, C10/11, G98/G99									
Safety / EMC	IEC 62109-1:2010, IEC 62109-2:2011, EN 61000-6-2:2005, EN 61000-6-3:2007/A1:2011									
General Data										
Dimensions (W x H x D)	481 x 395 x 195 mm									
Weight	12kg				13.5kg					
Operating Temperature Range	-30° C ~ +60° C									
Cooling Method	Natural									Smart Cooling
Protection Degree	IP66									
Max. Operating Altitude	4000m									
Relative Humidity	0 ~ 100%									
Topology	Transformerless									
Night Power Consumption	<1W									